

# WIRELESS MICROPHONE 860 MHz

## 8390015/ 860 MHz



RECEIVER	
Power Supply	12 to 24 V $\pm$ 20%
Maximun Intensity / Consumption	200 mA
Frequency range	UHF Range 780-960 MHz
Frequency Control	X-Quartz control
Stability	$\pm$ 0.005%
Maximun Desviation	$\pm$ 40 / 50 KHz
Dinamic Range	> 110 dB
Signal / Noise Relation	> 100 dB con $\pm$ 15kHz desviation
Frequency reponse	50 Hz - 15 kHz $\pm$ 3dB
TRANSMITTER	
Capsule	Dinamic
Antenna	Internal
Output Level	10 mW máx.
Battery	9 V ( more than 8 hours Alcalines)
RECEPTOR	
Alimentación	12 a 24 V $\pm$ 20%
Consumo Máximo	200 mA
Rango de frecuencia	UHF Rango 780-960 MHz
Control de Frecuencia	X-Quartz control
Estabilidad	$\pm$ 0.005%
Desviación máxima	$\pm$ 40 / 50 KHz
Rango dinámico	> 110 dB
Relación señal / ruido	> 100 dB con $\pm$ 15kHz desviación
Respuesta frecuencia	50 Hz - 15 kHz $\pm$ 3dB
TRANSMISOR	
Cápsula	Dinámico
Antena	Interna
Nivel de Salida	10 mW máx.
Batería	9 V

